



POZONE

Barcode Label Printer

BP2844



Key Features

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon internal diameter: 12.7mm (0.5")
- Bartender special edition



BP2844 Specification

BP2844 - Direct Thermal / Thermal Transfer Barcode Label Printer

Printing Method	Thermal Transfer/ Direct Thermal
Resolution	200 DPI
Interface	USB2.0 (Standard)/Bluetooth(Optional)/WIFI(Optional)/SD(Optional)
Real Time Clock	Optional
Max Print Speed	127mm (5")/s
Max Print Width	108mm (4.25")
Max Print Length	1778mm (70")
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	25.4mm-115 mm
Media Thickness	0.06 mm- 0.18 mm
Media Length	10 mm – 1778mm
Label Roll Capacity	127 mm (5") external diameter
Ribbon	Max length: 90M: Max roll diameter: 35mm: Internal diameter: 0.5" (12.7mm); Ribbon width: 25.4mm-110mm (1"-4.3")
Memory	8MB Flash Memory
	8MB SDRAM
	Micro SD Card reader for flash memory expansion, up to 4gb
Sensor	Gap Sensor
	Printer Head opened sensor
	Black mark sensor
	Ribbon end sensor
Processor	32-bit RISC CPU
Power Supply	Input: AC 100-240V; Output: DC 24V/2.5A
Barcode	1D Barcode: 1D barcode: Code 39, Code 93, Code 128UCC, Code128 subsets A, B, C Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
	2D Barcode: PDF-417, Maxicode, Datamatrix, QR code
Emulation	TSPL-EZ (EPL, ZPL, DPL)
Dimension	246x199x168mm (L*W*H)
Weight	1.62 kg
Safety Standard	FCC, CE, CB, CCC
Environment	Operation condition: -10-50 C (14-122 F), 10-90% non-condensing
	Storage condition : -40-60 C (-40-140 F), 10-90% non-condensing



POZONE

www.pozoneintl.com

Specifications are subjected to change without notice.

