

# DS-K1A802 Series Fingerprint Time Attendance Terminal



## **Available Models**

- DS-K1A802F-B (Fingerprint, Lithium Battery)
- DS-K1A802EF-B (EM Card, Fingerprint, Lithium Battery)
- DS-K1A802MF-B (M1 Card, Fingerprint, Lithium Battery)

### **Features**

- Person information structure: based on employee ID
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- Supports multiple languages: English, Vietnamese, Brazilian Portuguese, Spanish, French, Italian, Arabic, and Thai
- Accesses to public network via EHome 4.0 or 5.0 protocol, and sets EHome parameters on the client or device
- 2.8-inch LCD screen to display time, date, week, and attendance information
- Supports registering fingerprints from the terminal to software remotely
- Max. 3000 users, Max. 3000 fingerprints, and Max. 100,000 events records
- Two attendance authentication modes: authentication by person, authentication by device
- Stand-alone operation (supports adding persons, cards, and fingerprints locally)
- Exports the swiping card data and the attendance report to the USB flash drive
- Up to 32 normal shifts, 32 man-hour shifts, and 32 attendance holiday schedules
- Generates the attendance report automatically and views the attendance data easily
- The third party arming is available
- · IP address conflict detection
- Still works properly with Lithium battery when powering off





# Specifications

Model	DS-K1A802F-B	DS-K1A802EF-B	DS-K1A802MF-B
Storage	Up to 100,000 records, 150,000 attendance records	Up to 3000 valid cards, 100,000 records, 150,000 attendance records	
Operation system	Linux		
iVMS-4200	Support		
Fingerprint capacity	Up to 3000 fingerprints; up to 10 fingerprints for each person		
Card reading response duration	<1s		
Fingerprint recognition duration	<1s		
Fingerprint comparing mode	1:1 and 1:N		
FAR (False Acceptance Rate)	≤ 0.001%		
FRR (False Rejection Rate)	≤ 0.01%		
Fingerprint recognizer	Optical fingerprint recognizer module		
Card reading mode	/	EM card, including cards with special shapes; Supports reading card in metal environment	M1 card, including cards with special shapes; Supports reading card in metal environment
Card reading distance	1	0 to 5 cm	0 to 5 cm
Lithium battery	2000 mAh		
Transmission Rate	LAN: 10/100 Mbps self-adaptive		
Wi-Fi	Support		
USB interface	USB 2.0, type A		
LCD screen	2.8-inch 320 × 240 LCD-TFT display screen		
Keypad	Physical keys (no backlight)		
LED indicator	Power/status (red/green)		
Audio	1 buzzer, 1 loudspeaker		
Power supply	12 VDC/1 A		
Working temperature	-10 °C to +55 °C (14 °F to +131 °F)		
Working humidity	10% to 90% (no condensing)		
Application mode	Indoor		
Color	Black (included), gold (optional), silver (optional), white (optional)		
Dimension (L × W × H)	140 mm × 155 mm × 30 mm (5.51" × 6.01" × 1.18")		
Installation	Surface mounting, metal door mounting, desk stand		



## **Appearance**









White

Distributed by

1

**HIKVISION** 

### Headquarters

Nc.155 Qianne Road, Bitylang District, Hangshou 310051, China T +88-571-8807-5998 oversassbusiness@hikvision.com

Hikvision USA T+1-909-895-9400 salve.usa@hikvsion.com

Hikvision Australia T +01-2-H580-4233 salesau@hikvision.com

Hikvision India T+81-22-284(9900 sales@pramahikvision.com

Hikytelon Canada T+1-865-200-6690 sales.canada@hikyision.com

Hikvision Thalland T +062-275-8949 sales./thalland@Mikvision.com Hikvision Europe 1 +31-23-5542770 salas au@hikvision.com

Hikylsion Haly T +39-0438-6902 Info.h@hawsion.com

Hikylsion Brazil T +55 (1 1318-055) Latam.aupport@hkkylsion.com

Hilly Islan Turkey T +90 (2)6(52), 7070-7074 sizes to 20 Newton com

Hiloiston Halaysia T +601-7652-2913 salto my@hiloiston.com Hikvision UK & Ireland 1 +01628-902140 sides.uk@hikvision.com

Hikvision South Africa Tet: +27 (10) 0351172 sate africa@hikvision.com

Hikvision France T + 33001 -85-330-450 Into AsShekylsion.com

Hikvision Kazakhstan T.+7-727-9730667 nakla.panfilow@hikvision.ru

Atleviston Vietnam T +8=-97/27/0888 : submodu@hikviston.com Hikkleton UAE T +971-4-4452990 seiseme@hirvloicc.com

Hilodalon Singapore T +66-6684-4718 sqiilitrikMslon.com

Hilotolon Spain T + 34-93-737-18-55 Info,es@bhikvision.com

Hikytelon Tashkent 1 +99-87-1238-9436 urb@hikytslon.ru

Hikvision Hong Kong T+852-2151-1761 Info,hk@philvision.com Histolon Russia T + 7+495-580-67-99 sateru@244stsipn.com

HRvision Korea T +82-10(31-731-8817 sples.korea@hRvision.com

Hikvision Poland 1 + 48-22-450-01-50 vifo.pl@hkvision.com

Hikvision indonesia 1 +62-21-2933759 Sales Indonesia ((bhikvision.com

Hikvision Colorabia sales cotambia@Wikvision.com