

DS-KC001

Video Intercom Monitoring Tablet

HIKVISION



Key Feature

- 7-inch colorful touch screen with resolution 1024 × 600
- Remote temperature screening & records checking, real time preview
- Centralized data management, max to 100,000 records
- Abnormal temperature alarm
- Remote access control & video intercom


Approval

CE-EMC	a. EN 55032:2015 b. EN 61000-3-2:2014 c. EN 61000-3-3:2013 d. EN 50130-4:2011 +A1:2014
CE-LVD	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
CE-RED	a. EN 201 489-1 V2.1.1, EN 301 489-17 V3.1.1 b. EN 300 328 V2.1.1, EN 62311:2008
FCC-SDOC	47 CFR Part 15, Subpart B
FCC-ID	47 CFR Part 15, Subpart B
UL	UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07, Information Technology Equipment – Safety – Part 1: General Requirements


Specification

System parameters	
Memory	1 GB
Flash	4 GB
Operation system	Android 5.1
Display parameters	
Display screen	7-inch colorful TFT touch screen
Display resolution	1024 × 600
Operation method	Capacitive touch screen
Brightness	Adjustable
Audio parameters	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Volume	Adjustable
Consumption	0.5 W
Audio compression standard	G.711 U, G.711 A
Audio compression rate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Network parameters	
Wired network	10/100 Mbps self-adaptive
Wireless network	Wi-Fi 802.11 b/g/n
Network protocol	TCP/IP, Private SIP, RTSP
Interfaces	
Network port	RJ45
RS-485	1
Alarm in	8
TF card	Built-in 32 G TF card
Debugging port	1
General	
Power supply	12 VDC
Power consumption	≤ 5 W
Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Working humidity	10% to 90%
Storage humidity	0 to 95% (no-condensing)
Dimensions	200 mm × 140 mm × 15.5 mm (7.87" × 5.51" × 0.61")
Weight	419.3 g (without package)

Dimension



Appearance and Interfaces




No.	Description	No.	Description
1	Display Screen	5	Loudspeaker
2	Microphone	6	Alarm Terminals
3	Debugging Port	7	Power Interface
4	Network Interface		

Available Model

DS-KC001

Distributed by

**HIKVISION****Headquarters**

No.555 Dianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5888
evan@asbus.hose@hikvision.com

Hikvision USA
T +1-800-895-0100
sales.usa@hikvision.com

Hikvision Australia
T +61-2-9009-4033
sales.au@hikvision.com

Hikvision India
T +91-22-29469000
sales@promohikvision.com

Hikvision Canada
T +1-866-300-8800
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-8049
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-6540770
sales.eu@hikvision.com

Hikvision Italy
T +39-0439-6002
info.it@hikvision.com

Hikvision Brazil
T +55-11-3319-0750
latam.support@hikvision.com

Hikvision Turkey
T +90-2165217070-7079
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +41628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27110-0301172
sales.africa@hikvision.com

Hikvision France
T +3301-95-50-460
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-0730867
niks.parkov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vi@hikvision.com

Hikvision UAE
T +971-4-4432000
sales.me@hikvision.com

Hikvision Singapore
T +65-6086-6718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-65
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
Info.hk@hikvision.com

Hikvision Russia
T +7-495-669-07-69
sales.ru@hikvision.com

Hikvision Korea
T +82-10011-733-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com