



POZONE

Mobile Printer MP310B



Supports direct USB Charging
Long lasting Battery life
Dual mode bluetooth
OLED Screen available
TSPL, EPL, ZPL, DPL, CPL, ESC/ POS
command compatible

Applications



Shopping

Mart

Restaurant



Hospital

Coffee Shop


Ticketing

*Specifications are subject to change without notice

www.pozoneintl.com

MP310B

Mobile Label Printer



Printing

Resolution	203 DPI
Printing method	Direct Thermal
Max. print speed	Max. 70mm (2.7")/s
Max. print width	72mm (2.8")
Max. print length	1778mm (70")

Media

Media type	Continuous, gap, black mark
Media width	20mm ~ 76mm
Media thickness	0.06mm ~ 0.254mm
Label roll diameter	50mm

Performance Features

Processor	32-bit CPU
Memory	8MB Flash Memory / 8MB SDRAM
Interface	Standard version: USB + Bluetooth Optional: USB + WIFI
Screen	OLED (1.3") Resolution: 128*64 pixels
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor

Fonts/Graphics/Symbologies

Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, Data Matrix, QR code, Aztec
Rotation	0°、90°、180°、270°
Emulation	TSPL、EPL、ZPL、DPL、CPCL、ESC/POS

Physical Features

Dimensions	124×108×61mm (D×W×H)
Weight	357g

Reliability

Printer head life	30Km
-------------------	------

Software

Operating system	Windows / Android / iOS
SDK	Windows / Android / iOS

Power supply

Output	DC 9V/1A
Battery	7.4V/2600mAh

Environmental Conditions

Operation environment	5~40°C (41~104°F) , Humidity: 25~85% non condensing
Storage environment	-40~60°C (-40~140°F) , Humidity: 10~90% non condensing

*Specifications are subject to change without notice

