



POZONE



Mobile Printer MP410B



Applications



Shopping



Mart



Restaurant



Hospital



Coffee Shop



Ticketing

LCD screen, easy to operate



Low noise, high quality, high speed printing

2500mAh large capacity battery, long standby

TSPL, EPL, ZPL, DPL, CPCL, ESC/POS emulation compatible

MP410B

Mobile Label Printer



Printing

Resolution	203 DPI
Printing method	Direct Thermal
Max. prints peed	Max.100mm (3.937")/s
Max.printwidth	108mm (4.25")
Max.printlength	1778mm (70")

Media

Mediatype	Continuous, gap, black mark
Mediawidth	40mm~112mm
Mediatickness	0.06mm~0.254mm
Paperrolldiameter	50mm

Performance Features

Processor	32-bit CPU
Memory	8MB Flash Memory/8MB SDRAM
Interface	Standard version: USB+Bluetooth Optional: USB+WIFI/NFC
Screen	1.3" OLED
Sensors	① Gapsensor ② Coveropeningsensor ③ Blackmarksensor

Performance Features

Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D barcode	PDF-417, Maxicode, Data Matrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulation	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS

Physical Features

Dimensions	150mm (L)x131mm (W)x64mm (H)
Weight	0.45kg

Reliability

Printerheadlife	30Km
-----------------	------

Software

Operationsystem	Windows/Linux/Mac/Android/iOS
SDK	Windows/Android/iOS

Power supply

Input/Output	Input: AC100-240V, 0.5A 50-60Hz; Output: DC5V/2A
Battery life	7.4V/2500mAh

Options

Optional accessories	① Shoulders trap ② Protection bag ③ Dual-slot battery charger
----------------------	---------------------------------------------------------------

Environmental Conditions

Operation environment	5~40°C (41~104°F), Humidity: 25~85% non condensing
Storage environment	-40~60°C (-40~140°F), Humidity: 10~90% non condensing

*Specifications are subject to change without notice



POZONE
www.pozoneintl.com

