



◆ **Check Body temperature:**

- Check : Forehead center or wrist
- Deviation: 0.2℃~+0.5℃\
- Distance: 0.1-50CM
- Best Distance: 0.1-10CM
- Alarm for fever passenger
- Alarm value adjustable (Suggest 37.0℃)
- Multi-language voice to tell test results

◆ **Search for threats:**

- Two LED lights bars show threats location on the body
- Extremely high sensitivity to detect tiny threats
- Stable performance
- 6 or 18 zones overall inspection
- Count total pass through persons and alarm persons

### ◆ Technical specification:

- Electrical current: AC100V~240V 50/60Hz
- Power: 12W
- Work environment: -20°C~+45°C
- Gross Weight: 70kg
- Outer frame: 2220mm (h) x 820mm (w) X 500mm (d)
- Inner frame: 2000mm (h) X 700mm (w) X 500mm (d)

### ◆ Characteristic:

- Multiple target locations from head to toe.
- Advanced broadband detection technology: can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from Level 0 to 300
- High: Can detect a clip
- Low: Detect big metal articles such as: knife, gun, and copper, aluminum, zinc (more than 150g), ignoring metal in belt button, shoes.
- Shock proof to avoid false alarm
- Sound and light alarm
- Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- Tamper-Proof: operate program is protected by password.
- Adjustable operating frequencies---eliminate the potential effects from X-ray units, radios and other electrical interference sources.
- Mix distance between two Walk-thru: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
- Harmless to pregnant woman and heart pacemaker
- Remote control (Optional)
- (Optional)Connect with computer, camera, turnstile, et

### ◆ Standards & Certificates

- ISO9001 •ISO14001 •HSMS18001 •CE
- In accordance with: EN60950, WN50081-1, EN50082-1
- Electric safety: EN60950
- Anti-interference standard: EN50082-1
- FCC, RoHS
- Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center