



PP610

THERMAL RECEIPT PRINTER

PP610, with fashion design, wireless port available, support cutter auto calibration function, cutter life upgrade to 1.5 million, supports firmware update online(USB+LAN only), compatible with ESC/ POS.

- Printing method Direct thermal
- Column capacity 576 dots/line(adjustable by commands)
- Printing speed 200mm/s
- Interface USB+Serial / USB+Lan/ USB+Bluetooth/ USB+Wifi
- Printing paper 79.5±0.5mm
- Line spacing 3.75mm (Adjustable by commands)
- Weight 1.0 kg
- Dimensions 184 x140x142 mm (DxWxH)



Features

- Wireless port available
- Wall mount capable
- Cutter life upgrade to 1.5 million
- Support cutter auto calibration function
- Support firmware update online(USB+LAN only)

PP610

Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line(adjustable by commands)
Printing speed	200mm/s
Interface	USB+Serial / USB+Lan/ USB+Bluetooth/ USB+Wifi
Printing paper	79.5±0.5mm
Line spacing	3.75mm (Adjustable by commands)
Commands	Compatible with ESC/ POS
Character size	ANK, Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

Cutter

Auto cutter	Partial
-------------	---------

Barcode Character

Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128
Input buffer	64k bytes
NV Flash	256k bytes

Power

Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics

Weight	1.0 KG
Dimensions	184 ×140×142 mm (D×W×H)

Environmental Requirements

Work environment	Temperature (0~45°C) humidity(10~80%)
Storage environment	Temperature(-10~60°C) humidity(10~80%)

Reliability

Cutter life	1.5 million cuts
Printer head life	100KM