



SECUPUS
www.xraysecuscan.com

ELLIPTIC WALK THROUGH METAL DETECTOR

Model: SPW-500

**FOR INDOOR AND
OUTDOOR USE**



Introduction:

The SPW-500 is ideal for outdoor events or checkpoint locations that move frequently and features tool-free installation, weather-resistant protection (IP55) and ease of system use for screening personnel.

WALK-THROUGH GATE STRUCTURE: State-of-the-art, robust, washable and compact elliptical columns Protected against aging, weather and wear

Advantages:

- Stable performance, 6 detection zones, Weather-proof IP55 protection
- Extremely high sensitivity to find even tiny threats
- Operation way: keypad
- ISO9001 • ISO14001 • HSMS18001 • CE
- Certificate from Ministry of Public Security Safety and Police Electronic Products Quality Inspection Center
- In accordance with: EN60950-1, EN61000-6-1
- Electric safety: EN60950
- Anti-interference standard: EN61000-6-3
- FCC, RoHS
- Aesthetic, Unobtrusive and Light Weight
- Superior Detection and Throughput



SECUPPLUS
www.xraysecuscan.com

ELLIPTIC WALK THROUGH METAL DETECTOR

Technical Specification:

- Electrical current: AC100V~240V 50/60Hz
- Power: 30W
- Work environment: -20 C~+50 C
- Gross Weight: 70kg
- Outer frame: 2220mm (h)X820mm (w)X300mm (d)
- Inner frame: 1990mm (h) X700mm (w) X 300mm (d)

Standards & Certificates:

- Two LED light bars on both door panels: gives alarm corresponding to the height or human body.
- 6 Pinpoint zones to precisely identify multiple target locations from head to toe.
- Advanced broadband detection technology: can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from Level 0 to 100
- High: Can detect a coin
- Low: Detect big metal articles such as: knife, gun, and copper, aluminums, zinc (more than 150g), ignoring metal in belt button, shoes.

Characteristic:

- Shock proof to avoid false alarm
- Sound and light alarm
- Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- Tamper-Proof: operate program is protected by password.
- Adjustable operating frequencies---eliminate the potential effects from X-ray units, radios and other electrical interference sources.
- Mix distance between two Walk-thru: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
- Harmless to pregnant woman and heart pacemaker

Authorized Distribution & Marketed By

SURVEILLANCE
SECURITY SYSTEMS
FIRE CONTROLS

Banglow No: 1/4-H, Block 6, P-E-C-H-S, Near
Majid-e-Sulemania, Shahrah-e-Faisal. Karachi.
Tel: 021-34325114-116 | UAN: 0304-1119292
Fax: 34330703
www.surveillance.com.pk