



SECUPPLUS
www.xraysecuscan.com

ELLIPTIC WALK THROUGH METAL DETECTOR

Model: SPW-6PLUS

**FOR INDOOR AND
OUTDOOR USE**



Introduction:

The SWP-6PLUS is ideal for outdoor events or checkpoint locations that move frequently and features tool-free installation, weather-resistant protection (IP65) and ease of system use for screening personnel.

WALK-THROUGH GATE STRUCTURE : State-of-the-art, robust, washable and compact elliptical columns Protected against aging, weather and wear .

Unique features : Auto Scan environmental interference at site and anti-interference The display of the electronics module indicate readiness for operation, the level of interference and the signal magnitude from metal objects carried through the control zone of the metal detector.

Advantages:

- Weatherproof design (IP65 protection)
- Inner size as 72cm width (Less false alarm and better for big body passengers)
- Automatically Calibration
- Detect zone: 33 zones
- Aesthetic, Unobtrusive and Light Weight
- Superior Detection and Throughput
- Updated DSP technology, offers high sensitivity, immunity to false alarms, discrimination, uniform detection a bigger breakeven for the products

Alarm Setting:

- 1. Audio Alarm time range from 1s to 9s.
- 2. LED alarm last from 1s to 9s.
- 3. Alarm volume range from level 1 to 20.
- 4. Alarm tones: Change from 1 to F (16 different tones for choosing)



SECUPUS
www.xraysecuscan.com

ELLIPTIC WALK THROUGH METAL DETECTOR

Technical Specification:

- › Electric current: 110V to 240V ,50/60Hz
- › Power: <15W
- › Power supply DC 15V/4A
- › Work temperature: -28℃~+47℃
- › Storage temperature:-30℃~+60℃
- › Humidity: 0 to 95% non-condensing
- › Gross Weight: 55kg
- › Outer frame: 2230mm (h) x 930mm (w) X 300mm (d)
- › Inner frame: 2010mm (h) X 720mm (w) X 300mm (d)

General Specification:

- › High sensitivity, accurate alarm
- › Self-diagnostic procedures
- › DSP Digital processing technology
- › 300 sensitivity level adjustable
- › Friendly LCD operate interface, local language support.
- › Modular structure to easy after service
- › Available 100 operate frequency, enable max 100pcs WTMD work side by side.
- › Automatically adapt to the working environment.
- › Good performance in anti-interference ability.
- › Sound and light alarm
- › Adjustable Zone Sensitivity from 0-300 level
- › 5 levels security class
- › 30 programs
- › Calculate traffic flow and resultant alarms
- › Tamper-Proof: key lock and two level password
- › Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- › Control panel – for indication of the detected zone in alarm
- › Traffic management – number of persons that passed through, number of alarms.
- › Adjustable operating frequencies—eliminate the potential effects from X-ray units, radios and other electrical interference sources
- › Harmless to pregnant woman and heart pacemaker medical devices or devices with electromagnetic storage (CCTV Systems, notebooks etc.)
- › Programming or adjustment via built-in keypad
- › Detect speed: change from 1 to 100 person per minute
- › Working Channel: total 100 different channels to choose, to avoid interference for WTMD side by side.

Authorized Distribution & Marketed By


SURVEILLANCE
SECURITY SYSTEMS
FIRE CONTROLS

Banglow No: 1/4-H, Block 6, P-E-C-H-S, Near
Majid-e-Sulemania, Shahrah-e-Faisal. Karachi.
Tel: 021-34325114-116 | UAN: 0304-1119292
Fax: 34330703
www.surveillance.com.pk