



SECUPUS

www.xraysecuscan.com

WALK THROUGH METAL DETECTOR



Model : SPW-IIIC



6 ZONES TO PRECISELY IDENTIFY MULTIPLE TARGET LOCATIONS FROM HEAD TO TOE

Features:

- High sensitivity, economic model
- 6,12, 18 zones option
- Automatically calibration

Unique features : Auto Scan environmental interference at site and anti-interference : The display of the electronics module indicate readiness for operation, the level of interference and the signal magnitude from metal objects carried through the control zone of the metal detector

Technical Specification:

- Electric current: AC100V~240V 50/60Hz
- Power: 12W
- Work environment: -20℃~+45℃
- Gross Weight: 70kg
- Outer frame: 2220mm (h) x 820mm (w) X 500mm (d)
- Inner frame: 2000mm (h) X 700mm (w) X 500mm (d)



SECUPUS
www.xraysecuscan.com

WALK THROUGH METAL DETECTOR

Characteristic:

- 6 zones to precisely identify multiple target locations from head to toe
- Advanced broadband detection technology: can detect ferrous and non-ferrous articles.
- Sensitivity adjustable from level 0 to 299 (300 levels)
- High: Can detect a coin
- Low: Detect big metal articles such as: knife, gun, and copper, aluminums, zinc (more than 150g), ignoring metal in belt button, shoes.
- Shock proof to avoid false alarm
- Sound and light alarm, Audible tone and 8 different volumes adjustable, Bright LED visual alarm
- Intelligent traffic and alarm counters that calculate traffic flow and resultant alarms.
- Two LED light bars on both door panels: gives alarm corresponding to the height or human body.
- Tamper-Proof: operate program is protected by password.
- Adjustable operating frequencies---eliminate the potential effects from X-ray units, radios and other electrical interference sources
- Counter tracks the number of patrons that have passed through the detector, the direction of patrons and the number of alarms and calculates alarm percentage
- All setting are secured with a key lock and two levels of access codes (system password and password to adjust sensitivity) further security is accomplished with a cabinet lock which prevents unauthorized access to physical cables, connectors and electronics.
- Mix distance between two Walk-thru: 0.3 meters at low sensitivity, 0.5 meters at high sensitivity
- Harmless to pregnant woman and heart pacemaker.
- Remote control unit and built-in battery (Optional)
- 2-10 hours built-in battery option

Authorized Distribution & Marketed By


SURVEILLANCE
SECURITY SYSTEMS
FIRE CONTROLS

Banglow No: 1/4-H, Block 6, P-E-C-H-S, Near
Majid-e-Sulemania, Shahrah-e-Faisal. Karachi.
Tel: 021-34325114-116 | UAN: 0304-1119292
Fax: 34330703
www.surveillance.com.pk