



SECUPUS
www.xraysecuscan.com

X RAY BAGGAGE SCANNER

Description:

Model: SPX-5030C

SOFTWARE INTELLIGENT & SAFETY

SPX-5030C adopt Small footprint and lightweight design, mainly for inspecting mail, small parcels, personal items, clothing and shoes, etc

It meets the throughput demands of high-traffic settings, 720pcs bags per hour. And easy to operate for security professionals and operators who may not have technical backgrounds.

HIGH LIGHT

- Black white and Color display
- Windows 7 operation system
- with independent industrial computer
- Professional multi-function operation keyboard
- automatic save scanned image
- Reliable performance
- Friendly Image processing interface
- CE, FCC, ROHS certificates

TECHNICAL CHARACTERISTICS

- dual energy penetration system;
- new radiation protection technology;
- TIP program;
- Organic and inorganic imaging
- Clear and distinct image;

APPLICATION FIELD

- entertainment venues, tourist attractions, office buildings, shopping malls, factories, etc;
- suitable for security inspection of briefcase, hand luggage, postal parcels and other small package





SECUPUS
www.xraysecuscan.com

X RAY BAGGAGE SCANNER

Technical Parameters

Model : SPX-5030C

Tunnel size	504*320mm (W*H)
Conveyor speed	0.20m/s, bi-direction scan
Conveyor height	693mm
Max Load	100kgs
Wire Resolution	40AWG
Spatial resolution	vertical : diameter 1.0mm, horizontal : diameter 1.0mm
Steel Penetration	14mm
Monitor	17inch, resolution 1280*1024
X Ray generator anode voltage	100KV
Cooling/operation cycle	Oil Cooling /100%
X ray Dose per inspection	<0.16 μ Sv
Image processing	Color/black & white image,Negative Image, High Penetration, Super-enhancement, histogram equalization, check back/forward, Automatic save image
Zoom	Variable zoom up to 32X, support continuous magnification.
Image Checking	Continuous check back image
Storage capacity	Can store more than 100,000 image
Radiation leakage	<1 μ Sv/h (5cm away from fame,in full compliance with all international radiation safety requirements.
Film safety	In accordance with ASA/ISO1600 film safe standard
System function	F1,F2,F3 programmable key, high density alarm, TIP : date/time display, baggage Count,User management, System work timing, Radiation timing, self-inspection while power on, save and search image, automatically maintenance and diagnosis system, image recognition training.
Optional function	Video surveillance system, voltage stabilizer, UPS back up
Frame size	1199*728*1197mm (L*W*H)
Weight	280kg
Environment temperature/humidity	- 10°C ~+45°C / 5%~95% (non-condensing)
Storage temperature/humidity	- 40°C ~+60°C / 5%~95% (non-condensing)
Power	110-240VAC , 50/60HZ
Consumption	0.6KVA
Noise Level	<55db

Authorized Distribution & Marketed By

SURVEILLANCE
SECURITY SYSTEMS
FIRE CONTROLS

Banglow No: 1/4-H, Block 6, P.E.C.H.S, Near
Majid-e-Sulemania, Shahrah-e-Faisal. Karachi.
Tel: 021-34325114-116 | UAN: 0304-1119292
Fax: 34330703
www.surveillance.com.pk