

# DH-PFS3008-8GT-L

## 8-Port Unmanaged Gigabit Switch



- Supports eight 10/100/1000 Mbps adaptive ports.
- Small and light, it is easy to carry and has multiple chips embedded in it.
- Easy to operate.



Robust Design



Plug & Play



Optimized Performance



Easy Installation

### System Overview

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

### Functions

#### Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

#### Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

#### Optimized Performance

All ports can transmit streams at high speeds without delay.

#### Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

### Scene



Home



Shop



Dormitory



Meeting Room

## Specification

### Hardware

Included Power Adapter	Yes
Ethernet Port	8
Ethernet Port Speed	10/100/1000 Mbps
Description of Function Slots	Port 1–8: 8 × 10/100/1000 Base-T
Power Supply	5 VDC; 1 A
Operating Temperature	0 °C to +45 °C (+32 °F to +113 °F)
Operating Humidity	5%–95% (RH)
Storage Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Storage Humidity	5%–95% (RH)
Power Consumption	Idling: 0.5 W; Full load: 3.0 W

### Performance

MTBF	576.29 years
Switching Capacity	16 Gbit
Packet Forwarding Rate	11.904 Mpps
Packet Buffer Size	1.5 Mbit
MAC Table Size	2K

### General

Statics Protection	Air discharge: 8 kV Contact discharge: 4 kV
Lighting Protection	Common mode: 2 kV
Net Weight	0.16 kg (0.35 lb)
Gross Weight	0.29 kg (0.64 lb)
Product Dimensions	132.9 mm × 62.4 mm × 24.0 mm (5.23" × 2.46" × 0.94")
Packaging Dimensions	136.0 mm × 55.0 mm × 153.0 mm (5.35" × 2.17" × 6.02")
Casing Material	Plastic
Installation	Desktop mount
Certifications	CE; FCC

## Dimensions (mm[inch])

