

DS-A71024R/440 Series Storage System

Introduction

DS-A71024R/440 series storage system is a storage product with huge capacity and high-density design. A 4U chassis provides up to 440 TB capacity. Compared to general storage product, it reduces the total cost at up to 50%. iRAID technology realizes an intensive management for storage space and data, and protects the data security from substructure. Support periodic HDD replacement, which guarantees the product availability.



Key Feature

Huge Capacity and High Density

- A 4U chassis provides up to 440 TB capacity
- High-density design reduces the installation space requirement and transportation cost

Low consumption

For 20 TB enterprise HDD, lower consumption for each terabyte at 50%

Security and Reliability

- iRAID technology and N + M redundant mechanism allow up to 2 error HDDs in a single RAID
- HDD encryption technology protects data security by only allowing Hikvision device to read the data in HDD

Maintenance-Free

- Rebuild fault HDD on-demand
- HDD periodic automatic replacement

Stream Data Management Structure of High Performance

Based on the bottom layer management structure of the stream media, it solves the problem that the damaged file system will lead to file unreadability or loss and ensures no file fragments will be produced during overwriting

Direct Storage of Mixed Stream

- Supports mixed storage of video stream and SMART stream
- Supports camera access through protocols including RTSP, ONVIF, etc.

iRAID

Erasur encoding and iRAID technologies ensure data integrity even when 2 HDDs in a single RAID are failed. If the number of error HDD exceeds redundant limit, other HDDs can still be read and written

Abundant Application

- Continuous recording, manual recording, and alarm recording

User-Friendly Operation and Maintenance


- Supports one-key configuration to improve system configuration efficiency
- Raises device maintenance efficiency via abundant alarm management methods, like alarm via indicators, and emails.



Specification

Model		DS-A71024R/440
Performance	Video (2 Mbps stream + rebuilding)	400-ch
Controller	Processor	64-bit multi-core processor
	Cache	16 GB, extendable to 32 GB
Storage	HDD slot	24 (the device is packaged with 22 HDDs)
	Interface	SATA
	Capacity	Up to 20 TB per HDD
	RAID	iRAID, RAID5, RAID6
	Disk	Disk detection pre-alarm and repair
	Logical volume	Recording volume management
Recording	Recording type	Continuous recording, manual recording, and alarm recording
	Video protection	Video loss alarm
	Search and download	Log in storage system to search, play, and download videos. Support searching videos by time, and event type
Maintenance and Management	Management method	GUI based on web, serial port CLI, platform
	Alarm method	Audio, indicator, GUI
Network	Protocol	RTSP, ONVIF, HKSDK
External interface	Data network interface	4, 1000 Mbps Ethernet interface
	Management network interface	1, 1000 Mbps Ethernet interface
	SAS interface	1
	COM interface	1, RS-232
	USB interface	2 × USB 3.0, 2 × USB 2.0
	VGA interface	Supported (VGA and RS-232 interface cannot be used at the same time)
	IPMI interface	Supported
General	Power supply	100 to 240 VAC/47 to 63Hz, redundant power supply
	Power consumption (with HDDs)	≤ 369.8 W
	Environment temperature	<ul style="list-style-type: none"> ● Working: 5 °C to 40 °C (41 °F to 104 °F) ● Storing: -20 °C to +70 °C (-4 °F to +158 °F)
	Environment humidity	<ul style="list-style-type: none"> ● Working: 20% to 80% RH (non-condensing/frozen) ● Storing: 5% to 90% RH (non-condensing/frozen)
	Dimensions (W × D × H)	445 × 175 × 746 mm (17.5 × 6.9 × 29.4 inch)
	Weight (without HDDs)	≤ 40 kg (88.2 lb)

Physical Interface



No.	Name	No.	Name
1	Power module 1	8	SAS interface
2	COM interface	9	Data network interface 3
3	Two USB interfaces	10	Management network interface
4	Two USB interfaces	11	Power module 2
5	Data network interface 1	12	IPMI
6	Data network interface 2	13	Data network interface 4
7	VGA interface		

Available Model

DS-A71024R/440

Distributed by

**HIKVISION**

Headquarters

No.555 Dianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8907-5988
twrzasstbusiness@hikvision.com

Hikvision USA
T +1-908-825-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8540-4233
salesau@hikvision.com

Hikvision India
T +91-22-28408850
sales@prtmahikvision.com

Hikvision Canada
T +1-888-203-8690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9940
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0430-0902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3338-8050
Latin.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7076- 3074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2433
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sales.africa@hikvision.com

Hikvision France
T +33011-85-330-460
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730867
niko.pentilov@hikvision.ru

Hikvision Vietnam
T +84-874270868
sales.vi@hikvision.com

Hikvision UAE
T +971-4-4432000
salesme@hikvision.com

Hikvision Singapore
T +65-6584-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-36-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2153-1751
info.hk@hikvision.com

Hikvision Russia
T +7-495-859-67-99
salesru@hikvision.com

Hikvision Korea
T +82-1031-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com