

DS-K1T802 Series

Access Control Terminal

AVAILABLE MODELS

- DS-K1T802E (EM Card Only)
- DS-K1T802M (M1 Card Only)



MAIN FEATURES

- 32-bit processor
- Stand-alone operation management settings
- Supports offline working, and online upgrade
- Max. 3000 card number settings, and Max. 10000 event records
- Supports Mifare card recognition, and Mifare card number reading (DS-K1T802M)
- Supports ID card recognition, and ID card number reading (DS-K1T802E)
- 128×64 Dot Matrix STN screen for displaying time, date, and week
- Supports TCP/IP network communication
- Multi-authentication mode: card, card and password
- Supports exit button
- Supports duress alarm function, and self-defined duress password(card)
- Supports first card, remote open door, super card and super password. Super password would not be restricted by the schedule template. Super card must observe the permission schedule (excepts the NC status)
- Supports offline event alarm for insufficient storage, offline alarm, door unsecured alarm, force opening door alarm, door opening time out alarm etc.
- Supports self-defined number for eliminating alarm
- Supports multi types of card: normal/disabled/blacklist/patrol/super/duress
- Supports time synchronization via NTP, manual or automatic method
- Watchdog design
- Data can be permanently saved after power-off
- Client supports attendance function

SPECIFICATIONS

Parameters	Model	DS-K1T802E	DS-K1T802M
Processor		32bit	
Storage		Storage for 3000 Legal Card Information and 10,000 Event Records	
Communication type		TCP/IP	
Card type		EM Card	Mifare Card
Input interface		Exit Button × 1, Door Sensor × 1	
Output interface		Doorbell × 1, E-lock Output × 1	
Key board		13 Keys (0-9, *, #, Doorbell)	
Display screen		STN Screen (Resolution 128*64)	
LED Indicator		Communication/Status	
Voice prompt		Beeper	
Working voltage		12V DC	
Working current		0.17 A(without Load)	
Working Temperature		-20°C to 65°C (-4° F to 149° F)	
Working Humidity		10% to 90% (No Condensing)	
Dimension		126.5(L)mm×94.5(W)mm×24(H)mm (4.98" × 3.72" × 0.94")	