

**Deliver
Exceptional
Vision in Every
Moment**



Capture the details at
high sensitivity even in darkness

LNU3530R

5 MEGAPIXEL
NETWORK BULLET CAMERA

FEATURES

- High quality image with 5MP, CMOS sensor
- (2880*1620)@ 30/25fps; 4MP (2560*1440)@ 30/25fps; 3MP (2304*1296)@ 30/25fps; 2MP (1920*1080)@30/25fps
- H.265, H.264 HP / MP / BP, M-JPEG
- D-WDR technology enables clear image in strong light scene
- Built-in Mic
- Smart IR, up to 30m (98.4ft) IR distance
- IP67 protection
- Support PoE power supply

LNU3530R

5 Megapixel Network Bullet Camera



Model	LNU3530R
Camera	
Image Sensor	CMOS
Lens	.3.6mm@F1.2, AF automatic focusing lens
Min. Illumination	Colour:0.002lux (F1.2, AGC ON) - 0 lux with IR
Day / Night	IR-cut filter with auto switch (ICR)
IR LEDs	Smart IR
IR Distance	Up to 30m (98.4 ft) IR range
Image Setting	Configurable Brightness, Saturation, Contrast, HLC, Smart Defog, Corrida
WDR	D-WDR, AWB
DNR	2D - 3D
Video / Audio	
Video Compression	H.265, H.264 HP / MP / SP, M-JPEG
Resolution	Main Stream: 5MP (2880*1620), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;
Multi Streaming	3
ROI	4 zones
Privacy Mask	Yes (Up to 4)
Motion Detection	Yes
Video Analytics	Tripwire / Perimeter
Text Overlay	Yes
Audio Compression	G.711U, G.711A
Event	
Event Trigger	Motion Detection / IP Conflict / Port Alarm
Event Notification	Email, FTP
Pre/Post Event Buffering	Yes
Network	
Ethernet	1 x RJ45 10M/100M/1000M Base-TX Ethernet
Security	Password protection, IP filter
Open Protocol	ONVIF (Profile S)
Protocol	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE
Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+
Video Management	Mobile App (iPhone, iPad, Android)
Max. Connection	4 Level / 8 Users
General	
Power Source	DC12V, POE
Max. Power Consumption	Power consumption: Max 8.5W
Operation Temperature/Humidity	-40°C ~60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Standard Approvals	KC, LVD, CE
Language	Korean, Chinese, Japanese, English, Turkish, Spanish
Color / Material	Black & White / Diecasting
Ingress Protection	IP67