



NETWORK CAMERA

Model	LNU-5560R
Camera	
Image Sensor	5 MP CMOS
Lens	2.8 ~ 12 mm
Day / Night	Dual ICR
IR LEDs	-
IR Distance	50 m
Image Setting	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS
Video / Audio	
Compression	H.265 + H.265, H.264 HP/MP/BP, M-JPEG
Resolutions	60Hz : 1440p@25fps, QXGA@25fps, 1080p@30fps, 960p@30fps, 720p@30fps 50Hz : 1440p@25fps, QXGA@25fps, 1080p@25fps, 960p@25fps, 720p@25fps
Maximum Frame rate	2560 x 1920@30fps, 1920 x 1080@60fps
Multi-Streaming	3
ROI	(Region of interest) 4 Zones
Video Analytics	Tripwire/Perimeter/Missing&Foreign object/Crowd/Loitering/Fast Moving/Parking/Off-position/Blurred Image/Audio Offline/Screaming Detection
Text Overlay	Support
Audio Compression	G.711/G.726/ADPCM/AAC
2-way Audio	-
Event	
Event Trigger	Motion Detection/IP Conflict/MAC Conflict/Port Alarm
Event Notification	-
Pre/Post Event Buffering	Yes
Interface	
Analog Video Out	-
Audio In / Out	-
Alarm In / Out	-
SD Slot	-
Network	
Ethernet	RJ-45 10, 100 BASE-T
Security	Password protection, IP Filter
Open Protocol	ONVIF (Profile S)
Protocol	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE
Video Management Software	Mobile App (iPhone, iPad, Android)
Max. Connections	4 Level/8 Users
General	
Power Source	DC12V, AC24V, POE
Max. Power Consumption	15 W
Max. Input Current	890mA (AC24V), 980mA (DC12V), 260mA (PoE)
Operating Temperature / Humidity-30°C	-30°C ~ 60°C / 0% ~ 95%RH
Standard Approvals	KC, LVD, CE
Language	Korean, Chinese, Japanese, English, Turkish, Spanish
Color / Material	Black & White / Diecasting
Ingress Protection	IK10, IP66
Dimension	102.4mm x 96mm x 305mm
Weight	1.5kg (Camera Only)