



## NETWORK CAMERA

Model	RNUE-B301R
<b>Camera</b>	
Image Sensor	3 MP CMOS
Lens	3.6 mm fixed Lens
Min. Illumination	0.05 lux @ F1.2 (1/30 sec, 50 IRE)
Day / Night	Dual ICR
IR LEDs	-
IR Distance	30 m
Image Setting	Configurable Brightness, Saturation, Contrast, Flip Mode, HLC, Smart Defog, Corridor, EIS
<b>Video / Audio</b>	
Compression	H.265, H.264 HP/MP/BP, M-JPEG
Resolutions	60Hz: 1080p@30fps 50Hz: 1080p@25fps
Maximum Frame rate	30fps(2048 x 1536), 1280*720@60fps
Multi-Streaming	3
ROI	(Region of Interest) 4 Zones
Privacy Mask	Yes (Up to 4)
Motion Detectio	Yes
Video Analytics	Tripwire / Perimeter / Missing & Foreign object / Crowd / Loitering / Fast Moving / Parking / Audio Offline
Text Overlay	Support
Streaming on Motion	Yes
Audio Compression	Yes
2-way Audio	-
<b>Event</b>	
Event Trigger	Motion Detection / IP Conflict / Port Alarm
Event Notification	Email, FTP
Pre/Post Event Buffering	No
<b>Interface</b>	
Analog Video Out	-
Audio In / Out	-
Alarm In / Out	-
SD Slot	-
<b>Network</b>	
Ethernet	RJ-45 10, 100 BASE-T
Security	Password protection, IP Filter
Open Protocol	ONVIF (Profile S)
Protocol	IPv4/IPv6, HTTP, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, TCP, UDP, DHCP, PPPoE
Web Viewer	IE8, IE10, IE11, Chrome42 under version, Firefox3.5+
Video Management Software	Mobile App (iPhone, iPad, Android)
Max. Connections	4 Level/8 Users
<b>General</b>	
Power Source	DC12V, POE
Max. Power Consumption	5.2 W
Max. Input Current	520mA (DC 12V ), 170mA (PoE)
Operating Temperature / Humidity-30°C	-30°C~60°C/ 0% ~ 95%RH
Standard Approvals	KC, LVD, CE
Language	Korean, Chinese, Japanese, English, Turkish, Spanish
Color / Material	Black & White / Diecasting
Ingress Protection	IK10, IP66
Dimension	70.2mm × 72.6mm × 201.2mm
Weight	0.453kg (Camera Only)