

Artificial Intelligence Smart Network Video Recorder

Model: TCAINVR4001-FR

04 CHANNEL



Our products are designed with the latest security technologies and provide you with the opportunity to address your security issues with the most hi-tech solutions.



Information:

- Embedded Operation System
- Fashionable UI of Windows style
- Support H.265/H.264 of decoding
- Support output of HDMI/VGA
- Support maximum resolution 4*2MP
- Support 1 USB interface
- Support GB28181
- Configuring one SATA interface, support access 2.5 inch removable hard drive
- Support real-time comparison, Face playback, Face trajectory, quickly entering database of strangers, Face datab- ase synchronization, Stay and wander alarm, VIP Guest arrival, traffic statistic, Attendance statistics, Face playb- ack, Face path analysis
- Support cloud technology, easy to achieve its function by intelligent mobile phones



Artificial Intelligence Smart Bullet Camera

www.thecoptech.com

Specification:

Video interface		
Operation System	Embedded Linux	
Interface style	Windows interface style	
Face channels' number	Four channels	
Playback	Support 1-way main stream playback	
	Peripheral interface	
source	DC	
Network port	1*100M Single port	
Video interface	HDMI/VGA Dual output	
USB interface	1	
SATA interface	1	
	Intelligent face	
Real-time comparison	Support four-channels comparison at the same time	
Face database management	Support quickly entering database of strangers and synchronization for remote import of face database	
Face deploying	Support push blacklist alarm	
Face intelligent application	Stay and wander alarm , VIP Guest arrival, traffic statistic, Attendance statistics, Face playback, Face path analysis	
	Standard protocols	
Network protocol	Support TCP/IP, NTP, DHCP, UDP, SMTP, RTSP, DNS, HTTP, P2P	
National standard	Support GB28181	
Mobile	Android, IOS	



Artificial Intelligence Smart Bullet Camera

Generic parameter		
power supply	DC 12V/2A	
size	17.8*15.8*3.5	
Power consumption	<10W(without hard disk)	
suitable environment	temperature-20°C-45°C , humidity10%-90%	