



## THE COP TECHNOLOGY

Our products are designed with the latest security technologies and provide you with the opportunity to address your security issues with the most hi-tech solutions.

Model: **TCIPC302BFL36-AU**

### Features:

- 3MP CMOS
- Max 25fps@3MP
- H.265 /H.264/ MJPEG stream encoding
- D-WDR(upto 140dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 3.6mm Fixed Lens
- IR Range Upto 30 Mtrs
- Built-in Mic
- IP67 protection



Scan Web link



## 3 MP Network Bullet Camera

### SPECIFICATION:

Model	TCIPC302BFL36-AU
Image Sensor	3MP CMOS
Minimum Illumination	0.005Lux/ F1.4( Color), 0Lux/ F1.4(IR on)
Effective Pixels	2048(H) x 1536(V)
Body Type	Bullet
Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
White Balance	Auto/Sunny/Night/Outdoor/Customized
Lens	3.6mm
AGC Control	Auto/Manual
Video Compression	H.265/H.264/MJPEG
S/N Ratio	More than 50dB
Back Light Comp.	BLC/ HLC/ WDR(140dB)
Video Streaming	Main Stream: 3MP(1~50/60fps), Sub Stream: D1 (1 ~ 50/60fps), Third Stream: 1080P(1~50/60fps)
Video Output	1 port
Resolution	3MP(2048× 1536)/1080P(1920× 1080) / 720P(1280× 720) /D1(704× 576) /CIF(352× 288)
ICR	Auto(ICR)/Color/B/W
ROI	supports
Audio Input	1 Channel
Audio Output	1 Channel
Bit Rate	H.264: 40K ~ 10Mbps
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI
Smart Detection	Motion / ROI
Smart Phone	iPhone, iPad, Android Phone
IR Range	IR Range of 30 Mtr.
Operating Temperature	-30°C~+60°C , Less than 95%RH
Power Source	DC12V, PoE+ (802.3af)
Weatherproof Standard	IP67 & IK10



Scan Web link