



THE COP TECHNOLOGY

Our products are designed with the latest security technologies and provide you with the opportunity to address your security issues with the most hi-tech solutions.

Model: **TCIPC302DFL28-AU**

Features:

- 3MP CMOS sensor
- 2.8mm Fixed Lens
- Max 20fps@3MP
- Ultra 265, H.265, H.264, MJPEG
- Smart IR, up to 30m (98ft) IR distance
- Built-in Mic
- IP65 protection
- Support PoE power supply



Scan Web link



3 MP Network Dome Camera

SPECIFICATION:

| Model | TCIPC302DFL28-AU |
|-----------------------|--|
| Image Sensor | 3MP CMOS Sensor |
| Minimum Illumination | Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR |
| Body Type | Dome |
| Shutter Speed | Auto/Manual, 1/3(4)~1/100000s |
| Lens | 2.8mm Fixed Lens |
| AGC Control | Yes |
| Video Compression | H.265/H.264/MJPEG |
| S/N Ratio | More than 50dB |
| Back Light Comp. | BLC/ HLC/D- WDR(140dB) |
| Video Output | 1 Port |
| Resolution | 3MP(2048× 1536)/1080P(1920× 1080) / 720P(1280× 720) /D1(704× 576) /CIF(352× 288) |
| ICR | Auto(ICR)/Color/B/W |
| ROI | supports |
| Audio Input | 1 Channel |
| Audio Output | 1 Channel |
| Bit Rate | H.264: 40K ~ 10Mbps |
| Protocol | IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI |
| Smart Detection | Motion / ROI |
| Smart Phone | iPhone, iPad, Android Phone |
| IR Range | IR Range of 30 Mtr. |
| Operating Temperature | -30°C~+60°C , Less than 95%RH |
| Power Source | DC12V, PoE 48V |
| Weatherproof Standard | IP65 |



Scan Web link